

ACOUSTI-COAT

1. PRODUCT NAME

Florok Acousti-Coat

2. MANUFACTURER

The Chargar Corporation

299 Welton Street

Hamden, Connecticut 06517

203-562-9948 Fax : 203-562-2053

3. PRODUCT DESCRIPTION

Florok Acousti-Coat is a heavy bodied rubber based paint, in which is suspended millions of "punkey" sand like particles. Its pleasing heavy texture, provides a rough matty coating capable of absorbing sound. It cushions and diffuses harsh noise and "bounce back" similar to conventional acoustical tile.

BASIC USES

Designed originally for concrete ceiling which is often rough, porous and contoured. It will seal and hide fine cracks, voids, blemishes and discoloration's.

Florok ACOUSTI-COAT may be sprayed on almost every type of ceiling surface, such as;

- * Prestressed Concrete Plank or Building Members
- * Plaster or Dry-Wall
- * Wood or Acoustical Tile
- * Metal Ceiling Decks

ADVANTAGES

- * Does not contain asbestos
- * One coat usually sufficient

- * Reduces noise level as much as 50%
- * Applied by textured spray equipment
- * Fire Retardant Class A Flame Spread
- * White and Custom colors
- * Will not peel, flake or dust
- * Can be painted

4. TECHNICAL DATA

Acrylic resin and rubber additives

Flame retardent fillers

Passes ASTM - E 1042 Classification for Acoustically Absorptive materials applied by trowel or spray

Also passes ASTM -C-423

and ASTM-E-1041

Water based formula, water cleanup
VOC compliant

5. INSTALLATION

In most cases a primer is not necessary. It is recommended for dark, discolored surfaces, metal, wood taping compound, etc., as follows

- * Primer Sealer /ST for use on non water sensitive surfaces or stains
- * Primer Sealer /P for wet surfaces
- * Primer Sealer/M for metal surfaces
- * Primer Sealer/W for unprimed wood.

Coverage

Approximately 50 sq. ft per gallon

Available in 5 Gallon pails & 55 Gal.drums

Directions: Follow label directions for complete application. Surfaces must be clean,dry and structurally sound