



1010

NEOPRENE™ SUPER FLASH® CEMENT #99 Data Sheet



- Seal leaks on wet or dry surfaces, or through standing water
- Outperforms plastic roof cement
- Elongation - 250%
- Flexible & watertight for up to 30 years
- Repairs EPDM roofing
- 30 year performance warranty

DESCRIPTION: Black Jack® Neoprene™ Super Flash® Cement is a unique professional-grade elastomeric flashing and repair product that cures to a long lasting rubber membrane. This product remains flexible through extreme temperature ranges. It's non-sag properties and its exceptional adhesion guarantees that Super-Flash® is the ideal cement for the construction and repair of all flashing, parapet walls, coping and chimneys. This product is ideally suited for sealing cracks, holes and tears in built-up roofs (asphalt and coal tar) and modified bitumen single plys. It is an excellent cement for sealing laps in sheet metal roofs. It may also be used as a patch & repair for EPDM rubber sheets. This product is not intended for use as an adhesive.

SURFACE PREPARATION: Surfaces must be clean from oil, grease, and other foreign materials prior to application. The surface must be firm and free from loose material and dust. All loose nails must be driven in and capped with this Super-Flash® Neoprene Flashing Cement. On composition and built-up, flat roofs, open any breaks or blisters to be patched and permit to dry out before filling with this Flashing Cement.

APPLICATION: To be applied with a trowel or putty knife and may be tooled with a trowel or putty knife. Spread evenly and smooth out as much as possible. Apply to a minimum wet thickness of 1/4" but not apply at a thickness greater than 1/2" per single coat. Permit to dry 24 hours before coating with an Elastomeric Coating.

COVERAGE RATE: Covers approximately 8-10 sq. ft. per gallon, when applied 1/8" thick.

DO's and DON'Ts... Do apply in exterior applications only. Do wear protective clothing. Do not thin. Do not use for adhering shingle tabs or under roof felts and membranes.

CLEAN UP: Tools are best cleaned with Xylol, but paint thinner or mineral spirits will work on fresh product.

PRECAUTIONS: Protective clothing and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any Store product in the cargo area of vehicle, and secure over protective cloths to damage due to accidental spills. Do not store at temperatures above 100°F. This manufacturer also disclaims liability for flat surface application where poor drainage or water may prevail. Do not reuse empty containers.

DANGER!: HARMFUL OR FATAL IF SWALLOWED.
CAUTION!: KEEP OUT OF REACH OF CHILDREN
CAUTION!: FLAMMABLE

For exterior use only. Contains petroleum based products. Keep away from heat, sparks, and open flame. Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. (NIOSH/MSHA TC 23C or equivalent). Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Do not use in drinking water or food systems. Seal container when not in use. When transporting product, be sure lid is tight and product is kept upright and secure.

CALIF. PROP. 65 • CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ). WARNING: This product contains chemicals known to the State of California to cause cancer. Use proper protection and adequate ventilation, when using product.

See MSDS for more info

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Flash Point	87°F
Weight Per Gallon, lbs.	10.1 lbs.
Consistency	Trowel
Residue by Evaporation, %	50 min.
Cure Time	7-10 Days
Application Temperature	40° to 120°F
Clean Up Tools	Xylol

Approx. Shipping Weights: (Note: All approx. weights include container.)

12 tubes/case	7.9 lbs.
1 gallon	10.7 lbs.
3 gallons	32 lbs.

VOC=466 g/l (3.8 lb./ gal) Maximum.

Neoprene
Xylene
Chlorinated Paraffins

CAS# 9010-98-4
MIXTURE
MIXTURE



Chargar Corporation
299 Welton Street
Hamden, CT 06517

Phone: (203) 562-9948
Toll Free: (800) 922-4623
Fax: (203) 562-2053
answers@chargar.com

LIMITED WARRANTY: Gardner-Gibson, Inc. warrants that this product, when applied in accordance with our written directions in applications recommended by us as suitable for the product, is free of defects in material and workmanship for a period of 30 years from the date of purchase. If you notify us of such a defect and provide adequate proof of purchase during this warranty period, we will replace the defective product at no cost to you. This limited warranty is the sole and exclusive remedy for any such defective product.

THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESSED OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/ OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE, AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

