

CURE & SEAL WB 20

1. MANUFACTURED BY:

The Chargar Corporation
299 Welton Street
Hamden, Connecticut 06517
203-562-9948 Fax: 203-562-2053

2. PRODUCT DESCRIPTION

Cure and Seal WB 20 is a VOC compliant concrete curing compound and sealer. Cure and Seal WB 20 is an Emulsified Acrylic Polymer designed to provide solvent based performance from a water emulsion system. Films of Concrete Cure And Seal WB 20 are crystal clear, water white polymer film which is resistant to water, chemicals, and interior and exterior applications. Can be used as a cure and seal and also as a durable floor or wall sealer.

3. BASIC USES AND ADVANTAGES

- * GREAT ADHESION
- * CHEMICAL RESISTANT
- * QUICK DRYING
- * EXCELLENT WATER RESISTANCE
- * RESISTANT TO ALCOHOL'S
- * GREAT FLEXIBILITY
- * ALKALI AND ACID RESISTANT

4. TECHNICAL DATA

Composition: Acrylic Polymer Total Solids : 18% & 30% Formulas
Drying time: 1 to 2 Hours depending on Temp. Passes ASTM C309-7
AASHTO M148-78 ASTM156 types 1, 1D, & 2
Traffic bearing in 24 hours. Recoat in 24 hours.
Coverage: 200-400 square feet per gallon depending on the texture of the concrete and absorption rate and desired gloss. For high gloss apply two heavy applications. For Satin finish apply an even coat.

5. PRECAUTIONS

Concrete Cure and Seal WB 20 is a water based sealer, when used for interior applications some ventilation may be required. A paint like aroma will be noticed. Apply to fresh concrete 24 Hours after pouring in cool temperatures. In hot weather apply as soon as you can walk on the fresh concrete and there is no surface water. APPLY A TEST SAMPLE TO FRESH CONCRETE. IF BUBBLES APPEAR, ALLOW THE CONCRETE TO SET LONGER.

6. PACKAGING

WB 20 is available in 55 gallon drums, 30 gallon drums, 5 gallon pails, and 1 gallon jugs.

7. APPLICATION

Apply by low pressure sprayer roller and squeegee. Do not leave puddles. May be painted or tiled over. For questionable applications consult our technical dept.