



HYDROPOXY

Epoxy Emulsion system

PROTECTIVE COATING

Damp-Proof • Decorative

PRODUCT DESCRIPTION

FLOROK HYDROPOXY - Protective Coating is a two component, equal part epoxy emulsion compound of high solids content. When intermixed it cures to a hard, durable, semi-gloss coating.

Being of a heavy paint consistency, it is capable of sealing porous surfaces and bridging fine cracks, holes and voids.

Heavy veneer type application can withstand hydrostatic pressure. (Contact manufacturer for technical assistance.)

FORMULATIONS

FLOROK HYDROPOXY - Protective Coating is the most popular general purpose coating. However, it is also available in special types suitable for trowel on applications, or as an aggregate exposure treatment matrix to receive stone etc. (Contact manufacturer for additional information.)

COLORS

Standard colors are White and Standard Grey. Other colors available on special order.

SIZES

- 1 Gallon Unit
- 2 Gallon Unit
- 10 Gallon Unit
- 100 Gallon Unit

TECHNICAL DATA

Vehicle type	Epoxy
Pot life at 70°F.	1½ hrs.
Pot life at 90°F.	45 min.
Coverage sq.ft./gal.	100-150
Cure time-touch dry	½ hr.
Cure time-final strength	7 days
Storage	Keep from freezing
Reduction & clean-up	Water



USES

All masonry interior or exterior walls, above or below grade, basement walls and floors (within certain limitations), tunnels, shafts and concrete decks.

ADVANTAGES

- Seals walls and floors against dampness and water penetration.
- May be applied to dry or damp surfaces.
- Will accept any type paint or decorative coating.
- Odor free.
- Clean up with water.
- Applies by brush, roller or spray.
- One coat usually sufficient for ordinary jobs. For severe conditions or waterproof treatments 2 or more coats may be required.

LIMITATION

Temperature at time of application must be above 40°F.

Do not apply to frozen surface.

All epoxy resins and hardeners may cause eye or skin irritation. Use with care. Read safety warning data on label.

May be applied to damp surface, however seal off active water seepage with a hydraulic type cement such as Waterplug before applying HYDROPOXY.



THE CHARGAR CORPORATION

299 WELTON STREET • HAMDEN, CONNECTICUT 06511

TELEPHONE (203) 562-9948

PRODUCT No.

120