



Klere-Treat WB

Silane Penetrating Sealer

KLERE-TREAT WB IS A WATER BASED, CLEAR, BREATHABLE AND PENETRATING SEALER FOR CONCRETE AND MASONRY SURFACES. KLERE-TREAT WB PENETRATES THE SUBSTRATE AND CHEMICALLY BONDS WITH SILICA TO FORM A PERMANENT WATER REPELLENT MOLECULE WITHIN THE PORES OF THE MASONRY. KLERE-TREAT WB CHEMICALLY REACTS TO FORM A DEEP HYDROPHOBIC LAYER THAT PREVENTS WATER AND CONTAMINATES FROM ENTERING THE PORES OF THE MASONRY SURFACE AND CAUSING DETERIORATION.

Basic Uses

- USE TO SEAL PARKING GARAGES, STADIUMS, BRIDGE DECKS AND BUILDINGS AND COOLING TOWERS
- CONCRETE HIGHWAY ROAD SURFACES
- RAMPS AND BARRIERS
- NATURAL STONE, BLUESTONE, GRANITE, MARBLE
- HORIZONTAL AND VERTICAL SURFACES
- EXTERIOR OR INTERIOR
- ABOVE GRADE

Advantages/Special Features

- DEEP PENETRATION
- LOW VOC
- NO CHEMICAL SMELL, UV RESISTANCE
- EXCELLENT CHLORIDE ION RESISTANCE
- 100% MOISTURE VAPOR TRANSMISSION
- KEEPS SURFACE CLEAN

Coverage

- ON HORIZONTAL SURFACES THE COVERAGE RATE SHOULD BE 100 TO 250 FT² PER GALLON. A 5'x5' AREA SHOULD BE TESTED. A WET SOAKING PATTERN SHOULD BE APPLIED. DO NOT APPLY ON VERY WINDY DAYS. IF A PUDDLE FORMS SPREAD WITH A PAINT ROLLER. ON VERTICAL SURFACES, SPRAY FROM A BOTTOM UP SO THAT A 6" RUNDOWN IS ACHIEVED. APPLY 2 COATS WET ON WET APPLICATION.

Packaging- AVAILABLE IN

- 1 GALLON JUGS
- 5 GALLON PAILS
- 55 GALLON DRUMS
- 275 GALLON TOTES



Limitations

- Not intended for below grade waterproofing. Application temperature should be above 20°F. Allow for 2 hours to dry before getting wet. Do not apply on windy days. Allow surfaces to dry 24 hours after a rain.

The Chargar Corporation
299 WELTON STREET
HAMDEN, CT 06517

PHONE: (203) 562-9948

FAX: (203) 562-2053

www.chargar.com