



EPOXY

WATER-PROOFER

Applies Like Paint

Withstands TONS
of Water Pressure

PRODUCT DESCRIPTION

Florok EPOXY WATERPROOFER is a specially formulated heavy bodied thermo setting Epoxy Resin (Part A) when mixed with its ACTIVATOR (Part B) it becomes self curing and hardens to a ceramic like, non porous, impermeable film, natural.


Since it is 100% solids, it can be applied from a thin brush application to 1/16th or 1/8th inch thick cladding that can withstand tons of hydrostatic pressure.

ADVANTAGES

- Waterproof.
- Resistant to corrosion, most chemicals, alkalies and acids.
- At least four times tougher than the strongest concrete.
- Not effected by continuous submergence.
- Not effected by weather or temperature changes.
- Apply by brush, roller, squeegee, dipping or skin application.



WALLS



POOLS



TANKS

BASIC USES

Florok EPOXY WATERPROOFER is designed to be a heavy duty waterproof protective coating that seals porous surfaces, fine cracks and voids. (Sand may be added for wide crack filler.) Also, highly suitable for coating and lining tanks, submerged concrete units, troughs, pipe, utility ducts, etc. Excellent to seal off leaks in below grade basement wall areas.

SPECIFICATIONS:

Florok EPOXY WATERPROOFER has been tested in accordance to the following Specifications: ASTM C 881, C 882, C 883, C 884, C 900, D 570, D 1259.

SIZES

Available in:
1 Quart Units
1 Gallon Unit
4 Gallon Unit



THE CHARGAR CORPORATION

299 WELTON STREET • HAMDEN, CONNECTICUT 06511

TELEPHONE (203) 562-9948

PRODUCT No.

119.5