Epoxy Water Proofer

Florok Epoxy Waterproofer is a specially formulated heavy bodied thermo setting Epoxy Resin. When mixed with the activator it becomes self curing and hardens to a clear ceramic like, non porous impermeable film. Color packs can be added to pigment it. Since it is a 100% solids it can be applied from a thin brush application to a 1/16 or 1/8 inch thick cladding that can withstand tons of hydrostatic water pressure. Available in 1 quart, 1 gallon, 4 gallon units

Basic Uses

- FLOROK EPOXY WATERPROOFER IS DESIGNED TO BE A HEAVY DUTY WATERPROOF PROTECTIVE COATING THAT SEALS POROUS SURFACES, FINE CRACKS AND VOIDS. SAND CAN BE ADDED AND MADE INTO A MORTAR FOR WIDER CRACKS, OR FIBERGLASS MATTING LAYERS.
- FOUNDATIONS- INTERIOR AND EXTERIOR
- PRECAST CONCRETE TANKS, SUBMERGED CONCRETE UNITS, CONCRETE PIPES, CONCRETE AND METAL TROUGHS
- Potable water tanks, waste water tanks
- Fish ponds and waterfalls, reflective pools, swimming pools
- BALCONIES AND DECKS
- Bridge Columns

Advantages


- Waterproof and resistant to corrosion
- Four times stronger than concrete
- Not affected by Weather or Temperature
- APPLY BY BRUSH, ROLLER, SQUEEGEE

Test results- In accordance with following specs.

- ASTM C881, C882, C883, C884, C900, D75, D1259
- NSF Certified for use in potable water APPLICATIONS

COVERAGE RATES

- Smooth concrete surfaces- 100 ft²/gal
- Rough concrete surfaces- 80 ft²/gal
- Concrete block- 80 ft²/gal
- Brick, Cement Plaster, Metal- 100 ft²/gal



Color pack system

 Epoxy Waterproofer utilizes a color pack system for added coloring to the clear. One color pack per gallon unit is added to the Part A resin at the time of application. With over 60 colors, the Epoxy Waterproofer color chart is available to view online at http://www.chargar.com/Products/prod_na.html

The Chargar Corporation
299 Welton Street

Hamden, CT 06517

PHONE: (203) 562-9948

Fax: (203) 562-2053

www.chargar.com